



LED POWER SUPPLY DATASHEET

SL45-12VF(UE)

DESCRIPTION

high cost performance, short circuit and overload protection.Meet ClassII requirements,lifetime 30,000hrs.



Input

Items	Conditions	Request	Note
Input voltage	Ta	100-240Vac	--
Input frequency		50Hz/60Hz	--
Input current	25°C,rated input voltage, output with max. rated power	< 0.65A	--
Input power		< 60W	--
Efficiency		≥ 85%	--
Standby		25°C,rated input voltage, output without load	<0.5W
Inrush current	25°C,rated input voltage	<60A	peak
PF	25°C,rated input voltage, output max. rated power	≥0.9	--

Temperate and others

Item	Conditions	Request	Note
Operation temp.	--	-20-45°C	--
Relative humidity	--	45%-85%	--
Max. case temp.	--	90°C	--
Lifetime	Max.Ta,rated input voltage,output with max.rated power	30,000hr	--
Working noise	25°C,rated input voltage,output with rated power ,mute box background noise<35dB,pickup 10cm distance from products	yes	--

Protection

Items	Conditions	Request	Note
Open circuit	Ta, rated input voltage, no load	--	--
Over load	Ta ,0.94-1.06 times of input voltage, 1.5 times of rated power	yes	--
Short circuit	Ta ,0.94-1.06 times of input voltage	yes	--
Over temperature	Ta ,0.94-1.06 times of input voltage, temperature detected point more than 115 degree	yes	--
Over voltage	Ta ,0.94-1.06 times of input voltage,output voltage is 1.5 times of rated one	--	--
Auto recovery	Over load, short circuit revocation	yes	--
Latch off	over heat re-start after cut off	yes	--

Output

Items	Conditions	Request	Note
Startup time	25°C, rated input voltage,output with max. rated power	<0.5S	--
Output voltage and precision	Ta , rated input voltage, output with rated power	12V±5%	--
Output current range	Ta ,rated input voltage	0-3.75A	--
Output voltage wave	25°C, rated input voltage,output with max. rated power	180mV	Vp-p
Output overload	25°C,rated input voltage,output with 2 times LED load	yes	--
Output current and precision	Ta , rated input voltage, output with rated power	--	--
Rated output voltage range	Ta , rated input voltage,	--	--
Output current wave	25°C, rated input voltage,output with max. rated power	--	Ip-p
Dimming mode	--	--	--
Dimming range	--	--	--


Mechanical, mounting

Items	Conditions
Case material and size	Plastic case: 251 mm x 30mm x 16 mm
Mounting ways	Independent
Insulation type	Class II
IP grade	IP20
Input cables dimension	Terminal block
Output cables dimension	Terminal block
Output cables length	--

Standard

Items	Conditions
Safety	IEC61347-1、 IEC61347-2-13
Harmonic	IEC61000-3-2
EMI	IEC55015
EMS	IEC61547

● **Dimensions(mm)**



● **Wiring Diagram**

